



BARSKA®

LASER GREEN SIGHT

DESCRIPTION

The BARSKA Green Laser Sight is easy to use and is constructed with high grade Aluminum. Laser sight has been powder coated, to avoid scratching or chipping. Ideal for target shooting in daylight or low light conditions, and reaches up to 1000m at night.



WARNING: BE CERTAIN THAT YOUR FIREARM IS NOT LOADED AND POINTED AWAY FROM YOU IN A SAFE DIRECTION

ATTENTION: THIS BARSKA LASER SIGHT IS A POWERFUL TARGETING DEVICE THAT REQUIRES SPECIAL ATTENTION WHEN OPERATING.

CAREFULLY READ THE FOLLOWING INSTRUCTIONS AND SAFETY PRECAUTIONS BEFORE USING THIS PRODUCT.


CAUTION: UNAUTHORIZED USE MODIFICATIONS OF ADJUSTMENTS OR PERFORMANCE OF PROCEDURE OTHER THAN SPECIFIED HEREIN MAY RESULT IN DANGEROUS/HAZARDOUS RADIATION EXPOSURE.

LASER LIGHT: AVOID DIRECT EYE EXPOSURE.

WARNING KEEP OUT OF REACH OF CHILDREN.

DO NOT POINT LASER AT PEOPLE, PETS, SHINY/HIGHLY REFLECTIVE SURFACES, OR ANY OTHER OBJECT NOT INTENDED FOR DESIGNATED USE.

MOUNTING



Your laser sight is equipped with a Picatinny Rail. This rail will attach your laser to your firearm.

1. Slide the laser sight into the bore of the Picatinny rail.
2. Once the sight is in the rail tighten it in place by using an Allen wrench.
3. Slide the rail onto your firearm, then tighten it in place with a flathead screw driver.

BATTERY

This device is powered by one 3v (CR 123A) Lithium Battery.

1. Unscrew the cable switch by turning it counter clockwise
2. Insert the battery so that the positive pole of the battery faces out.
3. Replace the switch back on the laser sight. Turn clockwise to tighten the cable switch onto the sight. Make sure that you have screwed the switch on tightly.



WINDAGE & ELEVATION

Adjustments must be made in the shooter's position of the sight. This laser sight has been factory calibrated. Should you require adjusting the windage and elevation remove turret caps and see chart below to distinguish which of these knobs you need to turn and in which direction.



	Up	Down	Left	Right
Elevation	C	CC		
Windage			CC	C

CC: Counter Clockwise
C: Clockwise

ATTENTION

DO NOT attempt to adjust the screw on the outside of the laser (see image to the right).

Altering this screw may misalign your laser sight. This screw is for factory use only.



DO NOT attempt to adjust this screw. This screw is for factory use only.


ACCESSORIES INCLUDED

- 1 Picatinny Mount
- 1 Cable Switch
- 1 3v (CR123A) battery

TECHNICAL DATA

Visible Laser Class IIIA Laser Product

Length	138mm
Weight	210g
Tube Diameter	31mm
Dot Size	<15mm at 10m
Output Power	<5mW
Wavelength	532±10nm
Reach	1000m at night
Adjustment	Windage & Elevation
Housing Material	Aluminum Waterproof
Battery Type	CR123A Lithium



Diameter: 31mm

WARNING:

AVOID EXPOSURE
LASER RADIATION IS EMITTED
FROM THIS APERTURE

DANGER

LASER RADIATION
AVOID DIRECT EYE EXPOSURE



Max Output <5mW
WAVELENGTH 532nm
Class IIIA Laser Product

This product complies with 21 CFR chapter 1, subchapter L.

5mW Green Laser Sight
Model: AU10982
Made In China

BARSKA Optics
1721 Wright Ave,
La Verne CA, 91750 USA